



永亮塗料有限公司

EVER BRIGHT PAINT COATING SDN. BHD. (857753-V)

101-Q, LINTANG KAMPUNG JAWA, (NON FREE TRADE ZONE)

11900 BAYAN LEPAS, PENANG, MALAYSIA.

TEL : (604) 644-4197 / 644-4203 / 644-0362 FAX : (604) 644-4234

Email: ebpaint888@gmail.com

PRODUCT:- **NO. 1 – ACRYLIC STOVING PAINT**

No. 1 Acrylic Stoving Paint is a high class stoving paint generally applies to electrical appliance, automotive, high quality office equipment and computer casing etc. It has good weather, water & chemical resistance and long-lasting appearance.

- *PHYSICAL CHARACTERISTICS OF PAINT*

Color	: Wide Range
Texture	: From flat to high gloss
Specific Gravity	: 0.9 – 1.3
Solid Content	: 65% by weight

- *RECOMMENDATION FOR USE*

Surface Preparation	: Surface to be treated are recommended to undergo one cycle of phosphate pretreatment.
Theoretical Coverage	: 69g/m ² at 25 microns
Drying Time	: 20 minutes at 160°C (M.T.P.)
Viscosity	: 70-75KU at 25°C
Number of Coats	: 1 coat 1 bake preferable with primer
Application Method	: Air, Airless, Static Spray
Thinner	: No. 1 Acrylic Thinner
Thinner Ratio	: 20% to 30% by weight
Shell Life	: 6 months
Standard Packing	: 5 liters or 20 liters
Pencil Hardness	: 2H

Note: Do not handle treated surface with hand to avoid blistering. Keep can tightly closed and avoid direct sunlight and heat.