



永亮塗料有限公司

EVER BRIGHT PAINT COATING SDN. BHD. (857753-V)

101-Q, LINTANG KAMPUNG JAWA, (NON FREE TRADE ZONE)

11900 BAYAN LEPAS, PENANG, MALAYSIA.

TEL : (604) 644-4197 / 644-4203 / 644-0362 FAX : (604) 644-4234

Email: ebpaint888@gmail.com

PRODUCT:- **NO. 7 – ALKYD STOVING PAINT**

Stoving Paint No. 7 is a combination of alkyd and melamine resin with superior quality pigments widely used in electrical appliances industries, automotive, iron and steel furniture. It gives super brightness, weather resistance, water and chemical resistance and anti-corrosion.

- *PHYSICAL CHARACTERISTICS OF PAINT*

| | |
|------------------|---------------------------|
| Color | : Wide Range |
| Texture | : From flat to high gloss |
| Specific Gravity | : 1.3 |
| Solid Content | : 65% by weight |

- *RECOMMENDATION FOR USE*

| | |
|----------------------|---|
| Surface Preparation | : Surface to be treated are recommended to undergo one cycle of phosphate pretreatment. |
| Theoretical Coverage | : 69g/m ² at 25 microns |
| Drying Time | : 20 minutes at 130°C (M.T.P.) |
| Viscosity | : 70-75KU at 25°C – 30°C |
| Number of Coats | : 1 coat of Alkyd no. 7 primer |
| Application Method | : Air Spray |
| Thinner | : No. 7 Melamine Thinner |
| Thinner Ratio | : 20% to 30% by weight |
| Shell Life | : 6 months |
| Standard Packing | : 5 liters or 20 liters |

Note: Do not handle treated surface with hand to avoid blistering. Keep can tightly closed and avoid direct sunlight and heat.