



永亮塗料有限公司

**EVER BRIGHT PAINT COATING SDN. BHD.** (857753-V)

101-Q, LINTANG KAMPUNG JAWA, (NON FREE TRADE ZONE)

11900 BAYAN LEPAS, PENANG, MALAYSIA.

TEL : (604) 644-4197 / 644-4203 / 644-0362 FAX : (604) 644-4234

Email: ebpaint888@gmail.com

## PRODUCT:- **NO. 920 – PLASTIC PAINT**

Plastic Lacquer No. 900 is a fast drying lacquer based on thermoplastic acrylic resin. It is widely used in P.S. and A.B.S. products. It gives good adhesion, alcohol resistance and easy to apply.

- **PHYSICAL CHARACTERISTICS OF PAINT**

Color	: Wide Range
Texture	: Fat and gloss
Specific Gravity	: 1.17
Solid Content	: 50% by weight

- **RECOMMENDATION FOR USE**

Surface Preparation	: The surface must be free grease, oil, silicon and other contaminant. Keep surface dry when applying.
Theoretical Coverage	: 77g/m <sup>2</sup> (at no gloss)
Drying Time	: Dry to touch – 10 minutes Dry to handle – 2 hours (25°C – 30°C)
Viscosity	: 80KU at 25°C
Number of Coats	: 1 or 2 coats
Application Method	: Air Spray
Thinner	: 900 Thinner
Thinner Ratio	: 40% to 50% by weight
Standard Packing	: 4 Kgs and 18 Kgs

*Note: The above information are laboratory tested result based on P.L. No. 900 (White).*

*\*\* Also available No. 900-A for lead free products such as toys industry, food can industry etc.*

*Please Mix thoroughly before use. Keep lids tightly closed after use and avoid direct sunlight and heat.*